


The Nyx Family.



Nyx Earth

Earth to Low Earth Orbit and back.



Nyx Moon

Earth to Lunar Gateway and back.



Large & growing market.

Cargo to and from space stations and the Moon is a double-digit billion market opportunity.















€65 million raised.


From EQT Ventures, Partech, Cherry, Dassault family, and more.



Mission Bikini

Sketch to flight-ready in 9 months.

Sketch



Concept Design






Structure Arrival



AIT




Qualification





January 2022



June 2022

August 2022

September 2022





2022

Mission Possible

Built for controlled re-entry in 2 years.

2022

Draft design & heat shield forging

Detailed design & heat shield forging

July

December

May

July

Draft design & leak tests done

Proof pressure & leak tests done

Proof pressure & leak tests done

May

July

2023

Moved to Planegg;

2023

2023

Environmental tests; capsule is Capsule is 50% Thermal protection integrated; closed ready for flight ✓ bonding for the loop tests on HiL heat shield September February Summer

2024


2024





Nyx Earth

On-track for its first flight in Q4-2027.





Anchor clients signed.









Axiom Space

ESA

Starlab

May 2024

VAST

June 2024

September 2023

May 2024



...and we are a *driving force* in the *European* exploration ecosystem.

ESA LEO Cargo Return competition co-shaped and won.

€50 million in contracts won from ESA, CNES, DLR, etc.


Mission Requirements & Vehicle Characteristics

Mission requirements

- 10 times reusable.
- Quick turn around: refurbishment not more than 6 months from splashdown.
- Payload:
 - Pressurized from and back to Earth: 2,600 kg with potential to 3,000 kg
 - Unpressurized to the ISS: 1,400 kg
 - · Unpressurized disposal cargo from the ISS: 1,000 kg
- Growth potential for human spaceflight
- 5 missions per year.

Nyx Earth Spacecraft

- Mass: 13.4 tons including 4 tons of payload
- Two main assemblies:
 - Capsule
 - Service Module
- Dimensions: D 4m x H 7.3 m
- Thrust: 20 x 200 N bipropellant thrusters (8 for orbit control + 12 for attitude control)
- Delta-V: ~350-400 m/s for a mission to the ISS




Human Inspirator Preparatory Activities Step 1: End-To-End Architecture Study

Cargo and Crew transport to Earth Orbit, Lunar Orbit and Lunar Surface




Nyx Architecture

- LEO Cargo:
 - Nyx Earth Cargo
 - o Injected to LEO by Ariane 6
- LEO Crew:
 - Nyx Earth Crew
 - Injected to LEO by Ariane 6
- Gateway Cargo:
 - Nyx Moon Cargo
 - Injected to LTO by an improved Ariane 6
- Gateway Crew:
 - Nyx Moon Crew
 - Injected to LTO by a heavy European launcher
- Lunar surface Cargo:
 - Nyx Lander Cargo
 - Injected to LTO by a heavy European launcher
 - 1 additional launch with Nyx Tug
- Lunar surface Crew:
 - Nyx Lander Crew
 - Injected to LTO by a heavy European launcher
 - 1 additional launch with Nyx Tug




Building the Nyx Family

In order to optimize synergies within the development and maximize the use of common building blocks, the architecture is built around 3 base plates, on which we add functional bricks.




Capsule Base plate Capsule-like structure and aeroshape (3.7 height x 4 m diameter)



Service Module Base plate Cylindrical structure (4 m height x 4 m diameter)



Lander Base plate Cylindrical structure with a truncated cone extremity (14.5 m height x 4 m diameter)





Baseline Bricks



Propulsion Bricks



Thermal protection Bricks



Power Generation Bricks




On-orbit services Bricks




Recovery services Bricks



Crew support Bricks










ConOps and Staging strategies

Crew transport Earth <-> LEO

- Vehicle start of mission: Injection to LEO
- 2. Vehicle phasing with LEO Station
- Vehicle RDV & docking to LEO Station
- 4. Unloading of payload to LEO Station
- 5. Loading of payload from LEO Station
- Vehicle end of mission: undocking and de-orbit burn





LTO

NRHO


ΔV = 175 m/s
ΔV = 45 m/s
ΔV = 160 m/s

N.

ConOps and Staging strategies

Crew transport Earth <-> Gateway

- Vehicle start of mission: Injection to TLO
- Vehicle LTO to NRHO (incl RPOD to Lunar Gateway)
- 3. Unloading of payload to Gateway
- 4. Loading of payload from Gateway
- Vehicle end of mission: NRHO to Earth surface




2/2

ConOps and Staging strategies

Cargo transport Earth -> LLO -> Lunar Surface -> Gateway

- Vehicle start of mission: Injection to TLO
- 2. Tug start of mission: Injection to LTO
- 3. Vehicle LTO to LLO
- 4. Tug LTO to LLO
- 5. Tug RPOD to Vehicle
- Vehicle Docking and Refilling from Tug
- 7. Tug undocking from Vehicle
- 8. Vehicle LLO to Lunar Surface
- Unloading of payload to Lunar Surface
- Loading of payload from Lunar Surface
- 11. Vehicle Lunar Surface to LLO (incl RPOD to Tug)
- Tug + Vehicle LLO to NRHO (incl RPOD to Lunar Gateway)
- 13. Unloading of payload to Gateway
- End of mission: Tug+Vehicle NRHO to Heliocentric graveyard orbit



© The Exploration Company GmbH 2024 - The copyright in this document is vested in The Exploration Company GmbH. This document may only be reproduced in whole or in part, or stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying or otherwise, either with the prior permission of The Exploration Company GmbH (critical photocopy).


2/2

ConOps and Staging strategies

Crew transport Gateway <-> Lunar Surface

- Vehicle start of mission: Injection to LTO
- 2. Tug start of mission: Injection to LTO
- Vehicle LTO to NRHO (incl RPOD to Lunar Gateway)
- Tug LTO to NRHO (incl RPOD to Vehicle)
- Vehicle Refilling from Tanks & jettison of empty Tanks
- 6. Tug + Vehicle Gateway to LLO
- 7. Tug undocking from Vehicle
- 8. Vehicle LLO to Lunar Surface
- Unloading of payload to Lunar Surface
- Loading of payload from Lunar Surface
- Vehicle Lunar Surface to LLO (incl RPOD to Tug)
- Tug + Vehicle LLO to NRHO (incl RPOD to Lunar Gateway)
- 13. Unloading of payload to Gateway
- Tug end of mission: NRHO to Heliocentric graveyard orbit

Note: this mission requires a parallel Crew transport Earth <-> Gateway mission



© The Exploration Company GmbH 2024 - The copyright in this document is vested in The Exploration Company GmbH. This document may only be reproduced in whole or in part, or stored in a retrieval system, or transmitted in any form, or by any means electronic, mechanical, photocopying or otherwise, either with the prior permission of The Exploration Company Gm/H/Gr/N/Atordance with the terms of ESA Contract No. 4000141565/23/NL/GE.

Nyx Architecture Performances

Baseline strategy	Requirement	Nyx	
Cargo transport Earth <-> LEO			
Cargo mass way-in [kg]	300	0	4000
Cargo mass way-back [kg]	200	0	2600
Crew		0	0
Number of launches		3	1
Crew transport Earth <-> LEO			(to LEO)
Cargo mass way-in [kg]		0	2000
Cargo mass way-back [kg]		0	1000
Crew		3	4
Number of launches		3	1
Cargo transport Earth <-> Gateway			(to LEO)
Cargo mass way-in [kg]	200	0	2000
Cargo mass way-back [kg]	200	0	2000
Crew		0	0
Number of launches		3	1
Crew transport Earth <-> Gateway			(to LTO)
Cargo mass way-in [kg]		0	3000
Cargo mass way-back [kg]		0	1000
Crew		3	4
Number of launches		3	1
Cargo transport Earth -> LLO -> Lunar Surfa	ice -> Gateway		(to LTO)
Cargo mass way-in [kg]	500	0	5000
Cargo mass way-back [kg]	200	0	2000
Crew		0	0
Number of launches		3	2
Crew transport Gateway <-> Lunar Surface			(to LTO)
Cargo mass way-in [kg]		0	200
Cargo mass way-back [kg]		0	200
Crew		2	2
Number of launches		3	2
			(to LTO)

